




VERIFICATION

The undersigned, of the below address, hereby certifies that he/she well knows both the English and Japanese languages, and that the attached is an accurate English translation of the Japanese Patent application filed on August 30, 2002 under No. P2002-253852.

The undersigned declares further that all statements made herein of his/her own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signed this 19th day of February, 2008.

Signature:


Name: Shiro TERASAKI

Address: c/o Soei Patent & Law Firm Ginza First Bldg.,
10-6, Ginza 1-chome, Chuo-ku, Tokyo 104-0061
Japan

JAPAN PATENT OFFICE

This is to certify that the annexed is a true copy of the following application as filed with this Office.

Date of Application: August 30, 2002

Application Number: Japanese Patent Application
No.2002-253852

Applicant(s): HAMAMATSU PHOTONICS K.K.

Commissioner,
Patent Office

(Seal)



253852/2003

(Document Name) Patent Application
(Reference Number) 2002-0214
(Presentation Date) August 30, 2002
(Directly) Commissioner of the Patent Office
(IPC) G02B 27/10

(Inventor)

(Residence or Address)

c/o Hamamatsu Photonics K.K., 1126-1, Ichino-cho,
Hamamatsu-shi, Shizuoka Japan

(Name) Yujin ZHENG

(Inventor)

(Residence or Address)

c/o Hamamatsu Photonics K.K., 1126-1, Ichino-cho,
Hamamatsu-shi, Shizuoka Japan

(Name) Hirofumi MIYAJIMA

(Inventor)

(Residence or Address)

c/o Hamamatsu Photonics K.K., 1126-1, Ichino-cho,
Hamamatsu-shi, Shizuoka Japan

(Name) Hirofumi KAN

(Applicant)

(Identification Number) 000236436

(Name) HAMAMATSU PHOTONICS K.K.

(Attorney)

(Identification Number) 100088155

(Patent Attorney)

(Name) Yoshiki HASEGAWA

(Attorney)

(Identification Number) 100089978

(Patent Attorney)

(Name) Tatsuya SHIODA

(Attorney)

(Identification Number) 100092657

(Patent Attorney)

(Name) Shiro TERASAKI

(Attorney)

(Identification Number) 100107456

(Patent Attorney)

(Name) Naruto IKEDA

(Official Fee)

(Pre-Paid Master Note Number) 014708

(Amount to be paid) 21000yen

(Lists of the Article to be presented)

(Name of Article) Specification 1

(Name of Article) Drawing 1

(Name of Article) Abstract 1

(Proof Reading) Required

[Name of Document] Specification

[Title of the Invention] optical condenser device

[Claims]

[Claim 1] An optical condenser device comprising:

5 a first light source; a second light source; and
a first optical combining element for combining beams from
the first light source with beams from the second light source,

the first light source having a first semiconductor laser array
stack in which a plurality of semiconductor laser arrays, each having a
10 plurality of active layers aligned in parallel in a first direction, are
stacked in a direction perpendicular to the first direction, a first
collimator lens for deflecting a plurality of beams in a plane
perpendicular to the first direction, which beams are emitted from the
plurality of active layers, and a first optical path changing element for
15 receiving the beams deflected by the first collimator lens to rotate the
transverse section of each beam by substantially 90°,

the second light source having a second semiconductor laser
array stack in which a plurality of semiconductor laser arrays, each
having a plurality of active layers aligned in parallel in a second
20 direction, are stacked in a direction perpendicular to the second
direction, a second collimator lens for deflecting a plurality of beams
in a plane perpendicular to the second direction, which beams emitted
from the plurality of active layers, and a second optical path changing
element for receiving the beams deflected by the second collimator
25 lens to rotate the transverse section of each beam by substantially 90°,
and

the first optical combining element having a light transmitting portions for receiving and transmitting the beams emitted from the first optical path changing element and a light reflecting portions for receiving and reflecting the beams emitted from the second optical path changing element, said first optical combining element combining the beams transmitted through the transmitting portions with the beams reflected by the reflecting portions.

[Claim 2] The optical condenser device according to Claim 1, wherein

the light transmitting portion and the reflecting portion of the first optical combining element both have strip-like shapes elongated in the direction of stacking of the laser arrays, and

the first optical combining element is constructed by flat plates having the transmitting portion and the reflecting portion positioned alternately.

[Claim 3] The optical condenser device according to Claim 2, wherein

the first optical combining element is inclined at an angle of 45° with respect to the central axes of both the beams emitted from the active layers of the first light source and the beams emitted from the active layers of the second light source,

the front surface of the first optical combining element opposes the first light source, and

the back surface of the first optical combining element opposes the second light source.

[Claim 4] The optical condenser device according to Claim 1,

further comprising a third light source and a second optical combining element,

the third light source having a third semiconductor laser array stack in which a plurality of semiconductor laser arrays, each having a plurality of active layers aligned in parallel in a third direction, are stacked in a direction perpendicular to the third direction, a third collimator lens for refracting a plurality of beams in a plane perpendicular to the third direction, which beams are emitted from the plurality of active layers, and a third optical path changing element for receiving the beams refracted by the third collimator lens to rotate the transverse section of each beam by substantially 90°, and

the second optical combining element having one or more transmitting portions for receiving and transmitting the beams combined by the first optical combining element and reflecting portions for receiving and reflecting the beams emitted from the third optical path changing element to combine the beams transmitted through the transmitting portions with the beams reflected by the reflecting portions.

[Claim 5] The optical condenser device according to Claim 1, further comprising a third light source and a second optical combining element,

the third light source having a third semiconductor laser array stack in which a plurality of semiconductor laser arrays, each having a plurality of active layers aligned in parallel in a third direction, are stacked in a direction perpendicular to the third direction, a third collimator lens for deflecting a plurality of beams in a plane

perpendicular to the third direction, which beams are emitted from the plurality of active layers, and a third optical path changing element for receiving the beams refracted by the third collimator lens to rotate the transverse section of each beam by substantially 90° , and

5 the second optical combining element having one or more transmitting portions for receiving and transmitting the beams emitted from the third optical path changing elements and one or more reflecting portions for receiving and reflecting the beams combined by the first optical combining element to combine the beams transmitted
10 through the transmitting portions with the beams reflected by the reflecting portions.

[Claim 6] The optical condenser device according to Claim 4 or 5, wherein

15 the transmitting portions and the reflecting portions of the second optical combining element both have strip-like shapes elongated in the direction of stacking of the semiconductor laser arrays, and

 the second optical combining element is a flat plate having the transmitting portions and the reflecting portions positioned alternately.

20 [Claim 7] The optical condenser device according to Claim 6, wherein

 the second optical combining element is inclined at an angle of 45° with respect to the central axes of the beams combined by the first optical combining element and the beams emitted from the active
25 layers of the third light source,

 the front surface of the second optical combining element

opposes the first optical combining element, and

the back surface of the second optical combining element
opposes the third light source.

[Detailed Description of the Invention]

5 [0001]

[Technical Field of the Invention]

This invention relates to an optical condenser device that
generates a laser beam with high optical density.

[0002]

10 [Prior Art]

Semiconductor laser array stacks are known as laser elements
with high output. Examples of semiconductor laser array stacks are
disclosed in Japanese Laid-Open Publication No. 9 - 181376 and
Japanese Laid-Open Publication No. 2002 - 9385. FIG. 2 is a
15 perspective view showing an example of a semiconductor laser array
stack. FIG. 3 is a diagram showing a front end surface (light-
outputting surface) of a semiconductor laser array. As shown in FIG.
2, a semiconductor laser array stack 12 has a structure wherein a
plurality of semiconductor laser arrays 11 and a plurality of heat sinks
20 13 are positioned alternately. Heat sinks 13 cool laser arrays 11.
As shown in FIG. 3, in each semiconductor laser array 11, a plurality
of active layers 14 are aligned in parallel in the horizontal direction.

[0003]

[Problems to be Solved by the Invention]

25 In semiconductor laser array stack 12, due to laser arrays 11
being layered in the vertical direction, the plurality of active layers 14

are positioned in a matrix-like manner. Each active layer 14 emits laser light. The laser light emitted from these active layers 14 form a single beam. By positioning active layers 14 at a high density, a beam with high optical density is obtained. However in recent years, further improvement of the optical density is being desired.

[0004]

An object of this invention is to provide an optical condenser device capable of generating a laser beam with very high optical density.

[0005]

[Means for Solving the Problems]

An optical condenser device in accordance with this invention comprises: a first light source; a second light source; and a first optical combining element. The first light source has a first semiconductor laser array stack, a first collimator lens, and a first optical path changing element. In the first laser array stack, a plurality of semiconductor laser arrays, each having a plurality of active layers aligned in parallel in a first direction, are stacked in a direction perpendicular to the first direction. The first collimator lens refracts a plurality of beams in a plane perpendicular to the first direction, which beams are emitted from the plurality of active layers. The first optical path changing element receives the beams refracted by the first collimator lens to rotate the transverse sections of the beams by substantially 90°. The second light source has a second semiconductor laser array stack, a second collimator lens, and a second optical path changing element. In the second laser array

stack, a plurality of semiconductor laser arrays, each having a plurality of active layers aligned in parallel in a second direction, are stacked in a direction perpendicular to the second direction. The second collimator lens refracts a plurality of beams in a plane perpendicular to the second direction, which beams are emitted from the plurality of active layers. The second optical path changing element receives the beams refracted by the second collimator lens to rotate the transverse sections of the beams by substantially 90°. Here, the transverse section of a beam refers to a cross section taken substantially perpendicular to the axis of the beam. The first optical combining element combines the beams from the first light source with the beams from the second light source. The first optical combining element has one or more transmitting portions for receiving and transmitting the beams emitted from the first optical path changing element, and one or more reflecting portions for receiving and reflecting the beams emitted from the second optical path changing element. The first optical combining element combines the beams transmitted through the transmitting portions and the beams reflected by the reflecting portions.

[0006]

The beams from the first laser array stack and the beams from the second laser array stack are combined using the optical combining element. A laser beam with high optical density is thereby generated. Due to the refraction of the collimator lenses, the spread of the beams emitted from the active layers of the laser array stacks are restrained in the plane perpendicular to the direction in which the active layers

are aligned. When the transverse sections of the beams are rotated by substantially 90° by the optical path changing elements, the spread of the beams become restrained in the direction in which the active layers are aligned. As a result, the transverse section of each beam is in a shape that is long in the direction of stacking of the semiconductor laser arrays and short in the direction of alignment of the active layers. If the transmitting portions and the reflecting portions of the optical combining element are in a strip-like shape elongated in the direction of the stacking of the laser arrays, the beams emitted from the active layers will be received appropriately by the optical combining element even if positional deviation of the active layers occurs.

[0007]

[Embodiments]

Embodiments of this invention will now be described in detail with reference to the accompanying drawings. In the description of the drawings, the same elements will be provided with the same symbols and redundant description will be omitted. Further, as a matter of convenience in Drawings, the dimension and ratio of parts in drawn in Figures do not match with those in the following explanation.

[0008]

(First Embodiment)

FIG. 1 is a schematic perspective view showing an optical condenser device of a first embodiment in accordance with this invention. The optical condenser device of this embodiment is

configured of a first light source 10, a second light source 20, and an optical combining element 30.

[0009]

First light source 10 is configured of a single semiconductor laser array stack 12, a plurality of collimator lenses 16, and a plurality of optical path changing elements 18. These components are optically coupled to each other.

[0010]

FIG. 2 is a perspective view showing a semiconductor laser array stack. As shown in FIG. 2, semiconductor laser array stack 12 has a structure in which a plurality of semiconductor laser arrays 11 and a plurality of heat sinks 13 are positioned alternately in the z axis-direction. FIG. 3 is a diagram showing a front end surface (light-outputting surface) of a laser array 11. FIG. 4 is a diagram showing a front end surface of an active layer 14. Each laser array 11 has a plurality of active layers 14. Active layers 14 of a laser array 11 are aligned, within a width of 1 cm, in a single row along the y axis-direction at intervals of 300 μm to 500 μm . The cross section of each active layer 14 has a width of 100 μm to 200 μm and a thickness of 1 μm . FIG. 5 illustrate the angles of spread of a beam emitted from a laser array. As shown in FIG. 5, the angles of spread of the beam emitted from this active layer 14 is 30° in the thickness direction of active layer 14, in other words, in the vertical direction (z axis-direction), and 8° in the width direction of active layer 14, in other words, in the horizontal direction (y axis-direction).

[0011]

Heat sinks 13 cool laser arrays 11. Each heat sink 13 has a cooling water path that is formed by integrating plate-like members made of copper together. The cooling water is circulated inside this cooling water path.

5 [0012]

FIG. 6 is a perspective view showing a cylindrical lens as an example of collimator lens 16. As shown in Fig. 6, the collimator lens has 0.2 mm length in the x-axis direction, 2 mm length in the y-axis direction and 0.6 mm length in the z-axis direction. The cylindrical lens 16 has a strip shape along the y-axis direction. Lens surfaces of the cylindrical lens 16 faced to each other are parts of cylindrical implosion having a generating line along the y-axis direction.

[0013]

15 Though cylindrical lens 16 does not provide a refractive action in the plane containing the generating line direction, it provides a refractive action in the plane perpendicular to the generating line. Since the beams emitted from active layers 14 are large in the angle of spread in the vertical direction, as mentioned above, the spread of the beams must be restrained in order to improve the condensing efficiency. Cylindrical lens 16 is thus set so that the generating line of its output surface 161 will be orthogonal to the vertical direction (z axis-direction) of semiconductor laser array 11. The beams emitted from active layers 14 can thereby be collimated in the vertical direction, that is, can be collimated within a plane perpendicular to the
25 generating line of cylindrical lens 16. Collimator lenses 16 thus

collimate the vertical direction (z axis-direction) components of the beams emitted from the respective active layers 14. In order for efficient collimation, cylindrical lenses 16 are positioned close to active layers 14. Collimator lenses 16 are thus put in one-to-one
5 correspondence with laser arrays 11. That is, the number of collimator lenses 16 installed is equal to the number of laser arrays 11. Each collimator lens 16 is positioned so as to oppose a single laser array 11. Thus all the beams emitted from active layers 14 of each laser array 11 enter one of collimator lenses 16.

10 [0014]

FIG. 7 is a perspective view showing an example of first optical path changing element 18. Optical path changing element 18 is formed of glass, quartz, or other light transmitting material. The length in the x axis-direction is 1.5 mm, the length in the y axis-
15 direction is 12 mm, and the length in the z axis-direction is 1.5 mm. Optical path changing element 18 has a shape that is elongated along the y axis-direction.

[0015]

Optical path changing elements 18 rotate the transverse
20 sections of the beams collimated by collimator lenses 16 by substantially 90°. Optical path changing elements 18 are thus positioned so as to be in one-to-one correspondence with cylindrical lenses 16. That is, each optical path changing element 18 is positioned so as to oppose the corresponding one of collimator lenses
25 16. Thus all the beams emitted from each cylindrical lens 16 enter the corresponding one of optical path changing elements 18.

[0016]

Optical path changing element 18 has an input surface 180 and an output surface 181 that oppose each other. Input surface 180 has a plurality of oblique cylindrical surfaces that are aligned in parallel. The width of each oblique cylindrical surface is 0.5 mm. These oblique cylindrical surfaces extend at an angle of 45° with respect to the y axis-direction. The number of these oblique cylindrical surfaces is equal to the number of active layers 14. These oblique cylindrical surfaces are thus in one-to-one correspondence with active layers 14. Output surface 181 likewise has a plurality of oblique cylindrical surfaces of 0.5 mm width aligned in parallel. These oblique cylindrical surfaces also extend at an angle of 45° with respect to the y axis-direction and are in one-to-one correspondence with active layers 14. Thus all the beams emitted from active layers 14 of each laser array 11 enter the corresponding one of optical path changing elements 18.

[0017]

Another example of a optical path changing element is described, for example, in Patent Publication No. 3071360.

[0018]

As with first light source 10, second light source 20 is configured of a single laser array stack 22, a plurality of cylindrical lenses 26, and a plurality of optical path changing elements 28. These components are optically coupled to each other. Since the configurations of laser array stack 22, cylindrical lenses 26, and optical path changing elements 28 are the same as those of laser array

stack 12, cylindrical lenses 16, and optical path changing elements 18, respectively, detailed description of these components will thus be omitted. However, the orientation of second light source 20 differs from the orientation of first light source 10. Specifically, each of laser arrays 11, which constitute laser array stack 12, has the plurality of active layers 14 aligned in parallel in the y axis-direction. Meanwhile, each of laser arrays 21, which constitute laser array stack 22, have a plurality of active layers 24 aligned in parallel in the x axis-direction. Cylindrical lenses 26 are positioned along the x axis-direction in correspondence to active layers 24 of laser arrays 21. Likewise, optical path changing elements 28 are positioned along the x axis-direction in correspondence to active layers 24 of laser arrays 21.

[0019]

FIG. 8 is a plan view showing optical combining element 30. Optical combining element 30 is configured of a flat plate having a plurality of transmitting portions 32 and a plurality of reflecting portions 34 positioned alternately. Transmitting portions 32 and reflecting portions 34 have a strip-like shape with the same dimension. Transmitting portions 32 and reflecting portions 34 are rectangles elongated along the direction of stacking (vertical direction) of laser arrays 11 and 21. optical combining element 30 is a plate made of mainly transparent material. A light transmitting thin film is formed on the surface of each transmitting portion 32. Meanwhile, reflecting portions 34 receive the beams emitted from second optical path changing elements 28. A light reflecting thin film is formed on

the surface of each reflecting portion 34. Each of transmitting portion 32 receives the beam emitted from the optical path changing element 18. while, each of reflecting portion 34 receives the beam emitted from the optical path changing element 28..

5 [0020]

Optical combining element 30 is inclined at an angle of 45° with respect to central axes 15 of the beams emitted from active layers 14 of first light source 10. Optical combining element 30 is also inclined at an angle of 45° with respect to central axes 15 of the beams emitted from active layers 24 of second light source 20. The front surface of optical combining element 30 opposes first light source 10 and the back surface of optical combining element 30 opposes second light source 20.

10 [0021]

One transmitting portion 32 corresponds to a single column of active layers 14, which are positioned in matrix-like form in laser array stack 12 of first light source 10. All the beams emitted from each column of active layers 14 enter the corresponding one of transmitting portions 32. Meanwhile, each reflecting portion 34 corresponds to a single column of active layers 24, which are positioned in matrix-like form in laser array stack 22 of second light source 20. All the beams emitted from each column of active layers 24 enter the corresponding one of reflecting portions 34. All the beams emitted from active layers 14 of first light source 10 are transmitted through transmitting portions 32 of optical combining element 30. Meanwhile, all beams emitted from active layers 24 of

second light source 20 are reflected by reflecting portions 24 of optical combining element 30. As a result, these beams propagate in the same direction at the back surface side of optical combining element 30. These beams are mixed into a single combined beam 61 (See Fig. 1).

[0022]

The operations of the condenser device of the present embodiment will now be described with reference to FIG. 9 and FIG. 10. Here, FIG. 9(a) shows the transverse sections of the laser beams generated in active layers 14 or 24 and emitted therefrom. FIG. 9(b) shows the transverse sections of the beams emitted from active layers 14 or 24 and then transmitted through cylindrical lens 16 or 26. FIG. 9(c) shows the transverse sections of the beams transmitted through cylindrical lens 16 or 26 and then transmitted through optical path changing element 18 or 28. FIG. 10(a) shows the transverse sections of the beams emitted from first light source 10 and transmitted through optical combining element 30, which transverse sections are taken perpendicularly to their central axes 15. FIG. 10(b) shows the transverse sections of the beams emitted from second light source 20 and reflected on a light transmitting portion of optical combining element 30, which transverse sections are taken perpendicularly to their central axes 15. FIG. 10(c) shows the transverse section of combined beam 61 of the beams from first light source 10 and the beams from second light source 20, which transverse section is taken perpendicularly to the central axis of combined beam 61.

[0023]

As shown in FIG. 4, the length of the transverse section of active layer 14 or 24 in the vertical direction is no more than $1 / 100$ th the length of the transverse section in the horizontal direction. Thus, the beam has the transverse section elongated in the horizontal direction when being emitted from active layer 14 or 24 (See Fig. 9(a)). Even if the beam emitted from active layer 14 or 24 spreads somewhat prior to reaching cylindrical lens 16 or 26, the length in the vertical direction of the transverse section of this beam can be restrained to no more than $1 / 10$ th the length in the horizontal direction. The beam that enters cylindrical lens 16 or 26 thus also has the transverse section elongated in the horizontal direction.

[0024]

After the transmission through cylindrical lens 16 or 26, each beam is subject to the refraction in a plane perpendicular to the direction of the generating line of cylindrical lens 16 or 26. As a result, the vertical direction components of the beams are collimated (See FIG. 9(b)). Meanwhile, since the horizontal direction components of the beams are not subject to the refraction, the beams do not change in the angle of spread in the horizontal direction.

[0025]

After the transmission through first cylindrical lens 16, the beams emitted from active layers 14 enter first optical path changing element 18. Optical path changing element 18 rotates the transverse sections of these beams by substantially 90° about central axes 15 of the respective beams (See FIG 9(c)). The beams collimated in the vertical direction are thereby converted into beams collimated in the

horizontal direction. As a result, the beams do not spread in the horizontal direction. The transverse section of each beam is in a shape that is long in the vertical direction and short in the horizontal direction.

5 [0026]

As with the beams from the first light source, the vertical direction components of the beams emitted from active layers 24 of second light source 20 are collimated after being transmitted through second cylindrical lens 26. After the transmission through second
10 optical path changing element 28, these beams are converted into beams collimated in the horizontal direction.

In second light source 20, the beams do not spread in the horizontal direction. As with optical path changing elements 18, the transverse section of each beam emitted from optical path changing element 28
15 is in a shape that is long in the vertical direction and short in the horizontal direction.

[0027]

The beams emitted from optical path changing elements 18 and 28 travel toward transmitting portions 32 and reflecting portions
20 34 of optical combining element 30, respectively. Each of transmitting portions 32 and reflecting portions 34 has a shape elongated in the vertical direction. Each beam traveling from active layer 14 or 24 to transmitting portion 32 or reflecting portion 34 is adequately narrow in width in comparison to the width of each
25 transmitting portion 32 or reflecting portion 34. The beam emitted from each of active layers 14 and 24 is thus received within the range

of the width of each transmitting portion 32 or reflecting portion 34 of optical combining element 30. In laser array stacks 12 and 22, active layers 14 and 24 are aligned in a matrix-like manner in the horizontal direction and the vertical direction. As shown in FIG. 10A, the beams emitted from each column of active layers 14 are transmitted through the corresponding transmitting portion 32. Meanwhile, as shown in FIG. 10B, the beams emitted from each column of active layers 24 are reflected by the corresponding reflecting portion 34. The beams transmitted through transmitting portions 32 and the beams reflected by reflecting portions 34 form combined beam 61. As shown in FIG. 10C, the optical density of combined beam 61 equals to the sum of the optical density of the beams emitted from first light source 10 and the optical density of the beams emitted from second light source 20. Since the beams with high optical density from laser array stacks 12 and 22 are thus combined, it is possible to obtain a beam with very high optical density.

[0028]

In the above description, it is assumed that all active layers 14 and 24 are positioned at predetermined positions. However in actuality, active layers 14 and 24 can deviate from the predetermined positions in the process of stacking laser arrays 11 and 21 in assembling laser array stacks 12 and 22. In the present embodiment, combined beam 61 can be formed without the degradation of the optical density even in such a case. This will be described hereinafter.

[0029]

Since laser arrays 11 and 21 are manufactured precisely by semiconductor processes, the errors in the intervals in the horizontal direction of active layers 14 and 24 in laser arrays 11 and 21 are very small. However, since laser array stacks 12 and 22 are assembled by mechanical processes, the stacking intervals of laser arrays 11 and 21 can be non-uniform. In this case, the positions of active layers 14 and 24 deviate from the predetermined positions in the vertical direction. This positional deviation is normally approximately 50 μm .

[0030]

The operations of the optical condenser device of this embodiment in the case where the positional deviation in the vertical direction occurs in laser array stack 22 will now be described with reference to FIG. 11. Here, it is assumed that there is no positional deviation in laser array stack 12. FIG. 11(a) shows the transverse sections of the beams emitted from first light source 10 and transmitted through optical combining element 30, which transverse sections are taken perpendicularly to their central axes 15. FIG. 11(b) shows the transverse sections of the beams emitted from second light source 20 and reflected by optical combining element 30, which transverse sections are taken perpendicularly to their central axes 15. FIG. 11(c) shows the transverse section of combined beam 61 of the beams from first light source 10 and the beams from second light source 20, which transverse section is taken perpendicularly to the central axis of combined beam 61. In laser array stack 22, the secondarily stacked laser array 21 is deviated in the vertical direction

from the predetermined position. Thus, as shown in FIG. 11(b), the beams of the upper two rows are deviated in the vertical direction. However, even if there is such positional deviation, the beams are able to enter reflecting portions 34 because reflecting portions 34 have a shape elongated in the vertical direction. As a result, the beams from first light source 10 and the beams from second light source 20 can be combined appropriately as shown in FIG. 11C to provide high optical density.

[0031]

In the above description, it is assumed that there is the vertical direction positional deviation of active layers. In effect, the positional deviation of active layers is limited to that in the vertical direction in most cases. However, there is the possibility that active layers 14 and 24 can be slightly deviated in the horizontal direction from the predetermined positions in the process of assembling laser array stacks 12 and 22.

[0032]

The operations of the optical condenser device of this embodiment in the case where the positional deviation occurs in the horizontal direction in laser array stack 12 will now be described with reference to FIG. 12. Here, it is assumed that there is no positional deviation in laser array stack 22. FIG. 12(a) shows the transverse sections of the beams emitted from first light source 10 and transmitted through optical combining element 30, which transverse sections are taken perpendicularly to their central axes 15. FIG. 12(b) shows the transverse sections of the beams emitted from second

light source 20 and reflected by optical combining element 30, which
transverse sections are taken perpendicularly to their central axes 15.
FIG. 12(c) shows the transverse section of combined beam 61 of the
beams from first light source 10 and the beams from second light
source 20, which transverse section is taken perpendicularly to the
central axis of combined beam 61. In laser array stack 12, the
secondarily stacked laser array 11 has the positional deviation in the
horizontal direction. Thus, as shown in FIG. 12(a), the beams of the
second row are deviated towards the right. However, even if there is
such positional deviation, the beams are able to enter transmitting
portions 32. Due to the operations of optical path changing elements
18, the transverse sections of the beams that enter transmitting
portions 32 from active layers 14 have a shape that is long in the
vertical direction and short in the horizontal direction. The widths of
these beams are very narrow in comparison to the widths of
transmitting portions 32. Thus, even if there is slight positional
deviation in the horizontal direction in active layers 14, transmitting
portions 32 can receive the beams from active layers 14. As a result,
the beams from first light source 10 and the beams from second light
source 20 can be combined appropriately as shown in FIG. 12(c).

[0033]

As described in detail above, the optical condenser device of
this embodiment is able to generate a laser beam with very high
optical density because the beams from two semiconductor laser array
stacks 12 and 22 are combined using optical combining element 30.
Since each of transmitting portions 32 and reflecting portions 34 of

optical combining element 30 has a shape elongated in the vertical direction, the beams can be combined appropriately even if there is positional deviation of active layers 14 and 24 in the vertical direction.
[0034]

5 [Second Embodiment]

A second embodiment of this invention will now be described. FIG. 13 is a schematic perspective view showing an optical condenser device of this embodiment. Whereas the first embodiment is configured of two light sources and a single optical combining element, the present embodiment is configured of three light sources and two optical combining elements. Whereas beams emitted from two light sources are combined in the first embodiment, beams emitted from three light sources are combined in the present embodiment.

15 [0035]

The optical condenser device of the present embodiment is configured of a first light source 10, a second light source 20, a third light source 40, a first optical combining element 30, and a second optical combining element 50. The arrangements and positioning of first light source 10, second light source 20, and first optical combining element 30 are as described in relation to the first embodiment.

20 [0036]

Third light source 40 has the same structure of the first light source 10 and second light source 20. That is, third light source 40 is configured of a single laser array stack 42, a plurality of collimator

lenses 46, and a plurality of optical path changing elements 48. The configurations of laser array stack 42, collimator lenses 46, and optical path changing elements 48 are the same as those of laser array stacks 12 and 22, collimator lenses 16 and 26, and optical path changing elements 18 and 28, respectively.

These are optically coupled to each other. As shown in FIG. 2, semiconductor laser array stack 42 has a structure in which a plurality of semiconductor laser arrays 41 and a plurality of heat sinks 43 are positioned alternately in the z axis-direction. Each laser array 41 has a plurality of active layers 44. Heat sinks 43 cool laser arrays 41.

[0037]

Collimator lenses 46 collimates the vertical direction components of beams emitted from the respective active layers 44. Collimator lenses 46 are put in one-to-one correspondence with laser arrays 41. That is, the number of collimator lenses 46 installed is equal to the number of laser arrays 41. Each collimator lens 46 is positioned so as to oppose a single laser array 41. Thus all the beams emitted from active layers 44 of each laser array 41 enter one of collimator lenses 46.

[0038]

Optical path changing elements 48 rotate the transverse sections of the beams collimated by collimator lenses 46 by substantially 90°. Optical path changing elements 48 are thus also positioned so as to be in one-to-one correspondence with laser arrays 41 in order to efficiently convert the optical paths of the beams emitted from laser arrays 41. The number of optical path changing

elements 48 installed is thus also equal to the number of laser arrays 41. Each optical path changing element 48 is positioned so as to oppose the corresponding one of collimator lenses 46. Thus all the beams emitted from each cylindrical lens 46 enter the corresponding one of optical path changing elements 48. Each optical path changing element 48 has an input surface and an output surface that oppose each other. Both the input surface and output surface have a plurality of cylindrical surfaces. The number of these cylindrical surfaces is equal to the number of active layers 44 of a laser array 41. That is, these cylindrical surfaces are in one-to-one correspondence with active layers 44. Thus all the beams emitted from active layers 44 of each laser array 41 enter the corresponding one of optical path changing elements 48.

[0039]

The orientation of third light source 40 is the same as the orientation of second light source 20 and differs from that of first light source 10. Whereas each laser array 11 of first light source 10 has active layers 14 aligned in parallel in the y axis-direction, laser arrays 21 and 41 of second and third light sources 20 and 40 have active layers 24 and 44 aligned in parallel in the x axis-direction. Each cylindrical lens 46 is thus positioned along the x axis-direction in correspondence to active layers 44 of semiconductor laser array 41. Likewise, each optical path changing element 48 is positioned along the x axis-direction.

[0040]

As described with the first embodiment, the beams emitted

from first light source 10 are transmitted through transmitting portions of first optical combining element 30. Meanwhile, the beams emitted from second light source 20 are reflected by reflecting portions of first optical combining element 30. As a result, these beams propagate in the same direction at the back surface side of first combiner 30. These beams are mixed into a single combined beam 61(See Fig. 13).

[0041]

Second optical combining element 50 has the same configuration as first optical combining element 30. That is, second optical combining element 50 is configured of a flat plate having a plurality of transmitting portions and a plurality of reflecting portions positioned alternately. The transmitting portions and the reflecting portions are rectangles elongated in the direction of stacking (vertical direction) of the semiconductor laser arrays. More specifically, the transmitting portions and reflecting portions are formed on a single flat plate made of light-transmitting material, and are positioned alternately and in parallel to form stripes elongated in the z axis-direction. The transmitting portions of second optical combining element 80 receive combined beam 61 emitted from first optical combining element 30. Meanwhile, the reflecting portions of second optical combining element 50 receive beams emitted from optical path changing elements 48. Second optical combining element 50 is inclined at an angle of 45° with respect to the central axis of combined beam 61. Second optical combining element 50 is also inclined at an angle of 45° with respect to the central axes of the

beams emitted from active layers 64 of third light source 40. The front surface of optical combining element 50 opposes first optical combining element 30 and the back surface of second optical combining element 50 opposes third light source 40. Each reflecting portion of second optical combining element 50 corresponds to one of the columns of active layers 44 that are positioned in a matrix-like form in third light source 40. All the beams emitted from each column of active layers 44 enter the corresponding one of the reflecting portions.

[0042]

Combined beam 61 passes through the transmitting portions of second optical combining element 50. Meanwhile, The beams emitted from third light source 40 are reflected by the reflecting portions of second optical combining element 50. As a result, these beams propagate in the same direction at the back surface side of second optical combining element 50. These beams are mixed into a single combined beam 65 (See Fig. 13).

[0043]

The operations and advantages of the optical condenser device of this embodiment will now be described. FIG. 14 shows that beams emitted from three light sources 10, 20 and 30 are combined by two optical combining elements 30 and 50 to form one combined beam 65. FIG. 14(a) shows the transverse sections of the beams emitted from first light source 10 and transmitted through optical combining element 30, which transverse sections are taken perpendicularly to their central axes 15. FIG. 14(b) shows the

transverse sections of the beams emitted from second light source 20 and reflected by optical combining element 30, which transverse sections are taken perpendicularly to their central axes 15. FIG. 14(c) shows the transverse sections of the beams emitted from third light source 40 and reflected by optical combining element 50, which transverse sections are taken perpendicularly to their central axes 15. FIG. 14(d) shows the transverse section of combined beam 61 of the beams from first light source 10 and the beams from second light source 20, which transverse section is taken perpendicularly to the central axis of combined beam 61. FIG. 14(e) shows the transverse section of combined beam 65 of the combined beam 61 and the beams emitted from third light source 40, which transverse section is taken perpendicularly to the central axis of combined beam 65.

[0044]

As described with the first embodiment, the beams transmitted through transmitting portions 32 (see FIG. 14(a)) and the beams reflected by reflecting portions 34 (see FIG. 14B) form combined beam 61 (see FIG. 14(d)). Combined beam 61 is transmitted through the transmitting portions of second optical combining element 50.

[0045]

Meanwhile, the beams emitted from optical path changing elements 48 of third light source 40 are reflected by the reflecting portions of second optical combining element 50. The beams emitted from each column of active layers 44 positioned in matrix-like form in laser array stack 42 are reflected by the corresponding reflecting portion (see FIG. 14(c)). Combined beam 61 transmitted

through the transmitting portions and the beams reflected by the reflecting portions form combined beam 65. The optical density of combined beam 65 equals to the sum of the optical density of the beams emitted from first light source 10, the optical density of the beams emitted from second light source 20, and the optical density of the beams emitted from third light source 40 (see FIG. 14(e)). Since beams with high optical density from semiconductor laser array stacks 12, 22, and 42 are thus combined, it is possible to obtain extremely high optical density.

[0046]

The positional deviation can occur in laser array stack 12, 22, or 44; however, as in the first embodiment, second optical combining element 50 also has the transmitting portions and the reflecting portions elongated in the vertical direction. Thus combined beam 65 can be formed without degradation of the optical density even if there is the positional deviation in the laser array stacks.

[0047]

The invention has been explained in detail hereinabove based on the embodiments thereof. However, the invention is not limited to the embodiments, and various modifications are possible without departing from the scope of the invention.

[0048]

In the embodiments described above, a cylindrical lens is cited as an example of a collimator lens; however, a glass fiber lens or a SELFOC lens, etc., may be used instead. Also, this invention may be an optical condenser device using four or more light sources.

[0049]

In the above-described optical combining elements 30 and 50, transmitting portions 32 and reflecting portions 34 of strip-like planar shape are positioned alternately. In place of such an optical combining element, an optical combining element 70 shown in FIG. 15 may be used. Optical combining element 70 has rectangular transmitting portions 72 positioned in matrix-like form, and lattice-like reflecting portions 74 placed between transmitting portions 72. Also, instead of reflecting portions 74, transmitting portions 72 may have a lattice-like shape and reflecting portions 74 may be rectangular.

[0050]

In the second embodiment, combined beam 61 is transmitted through second optical combining element 50 and the beams emitted from third light source 40 are reflected by second optical combining element 50 to form combined beam 65. However, combined beam 65 may be formed by causing the beams emitted from third light source 40 to be transmitted through second optical combining element 50 and reflecting combined beam 61 using second optical combining element 50. In this case, the transmitting portions of second optical combining element 50 receive the beams emitted from third optical path changing element 48. Meanwhile, the reflecting portions of second optical combining element 50 receive combined beam 61.

[0051]

With the first embodiment, an example is described in which the positional deviation occurs in either the laser array stacks of first light source 10 or the laser array stacks of second light source 20.

However, in the present invention, combined beam 61 can be formed even if the positional deviation occurs in the vertical direction and / or the horizontal direction in two or more of the laser array stacks.

[0052]

5 [Merit of the Invention]

The optical condenser device in accordance with the present invention is able to appropriately combine beams emitted from a plurality of semiconductor laser array stacks using an optical combining element to generate a laser beam with very high optical
10 density. The optical condenser device of this invention can thus be applied favorably to solid laser pumping, printing, material processing, and medical applications that require high optical density.

[Brief Description of the Drawings]

[FIG. 1]

15 This is a schematic perspective view showing an optical condenser device of a first embodiment.

[FIG. 2]

This is a perspective view of a semiconductor laser array stack used in the first embodiment.

20 [FIG. 3]

This shows a front end surface (light-outputting surface) of a semiconductor laser array used in the first embodiment.

[FIG. 4]

This shows a front end surface of an active layer of the
25 semiconductor laser array.

[FIG. 5]

This illustrates the angles of spread of a beam emitted from the semiconductor laser array.

[FIG. 6]

This is a perspective view of a cylindrical lens used in the first embodiment.

[FIG. 7]

This is a perspective view of a optical path changing element used in the first embodiment.

[FIG. 8]

This is a plan view of an optical combining element used in the first embodiment.

[FIG. 9]

This is a diagram illustrating the transverse sections of the beams in the first embodiment.

[FIG. 10]

This is a diagram illustrating combining of the beams in the first embodiment.

[FIG. 11]

This illustrates the combining of the beams when positional deviation of the active layers occurs in the vertical direction.

[FIG. 12]

This illustrates combining of the beams when positional deviation of the active layers occurs in the horizontal direction.

[FIG. 13]

This is a schematic perspective view showing an optical condenser device of a second embodiment.

[FIG. 14]

This is a diagram illustrating combining of beams in the second embodiment.

[FIG. 15]

5 This shows another example of an optical combining element used in an optical condenser device in accordance with this invention.

[Explanation of Reference Characters]

10... first light sources, 12... first semiconductor laser array stack,
14,24... active layer, 16... first cylindrical lens, 18... first optical
10 path changing element, 20... second light source, 22... second
semiconductor laser array stack, 26... second cylindrical lens, 28...
second semiconductor laser array stack, 30... first combining element,
32... light transmitting portion, 34... light reflecting portion, 61...
combined beam.

[Name of Document] Written Abstract

[Abstract]

[Problems]

To provide an optical condenser device capable of generating a
5 laser beam with very high optical density.

[Means for solving the Problems]

An optical condenser device has light sources 10, 20 and an
optical combining element 30. Each light source 10, 20 includes a
semiconductor laser array stack 12, 22, collimator lenses 16, 26, and
10 optical path changing elements (18, 28). Since the optical
combining element 30 combines the beams from one 12 of the stacks
and the beams from the other 22, a laser beam with high optical
density is generated. The optical combining element (30) has
transmitting portions 32 and reflecting portions 34, each of which
15 preferably has a strip-like shape elongated in the layering directions of
the stacks 12, 22. In this case, the beams emitted from the active
layers 14, 24 will be received and combined appropriately by the
optical combining element 30 even if positional deviation of the
active layers 14, 24 occurs.

20 [Selected Figure] Fig. 1